


DG S CI 275 (952 079)


- Arrester backup fuse integrated in the protection module
- Prewired complete unit consisting of a base part and plug-in protection modules
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG S CI 275



Dimension drawing DG S CI 275

Pluggable single-pole surge arrester consisting of a base part and plug-in protection module; with integrated backup fuse; optionally available with floating remote signalling contact

Type	DG S CI 275
Part No.	952 079
SPD according to EN 61643-11	Type 2
SPD according to IEC 61643-1/-11	Class II
Max. continuous operating a.c. voltage (U_c)	275 V
Nominal discharge current (8/20 μ s) (I_n)	12.5 kA
Max. discharge current (8/20 μ s) (I_{max})	25 kA
Voltage protection level (U_p)	≤ 1.5 kV
Voltage protection level at 5 kA (U_p)	≤ 1 kV
Response time (t_a)	≤ 25 ns
Max. mains-side overcurrent protection	not required
Short-circuit withstand capability	25 kA _{rms}
Temporary overvoltage (TOV) (U_T)	335 V / 5 sec.
TOV characteristic	withstand
Operating temperature range (T_U)	-40°C...+80°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm ² solid/flexible
Cross-sectional area (max.)	35 mm ² stranded/25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	1 module(s), DIN 43880
Approvals	KEMA, VDE
Weight	141 g
Customs tariff number	85363030
GTIN	4013364128446
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.