



DG S 275 VA (952 082)

- Multi-purpose surge arrester consisting of a base part and plug-in protection module
- Leakage-current-free series connection of a varistor and a spark gap in the pluggable protection module
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG S 275 VA

Dimension drawing DG S 275 VA

Modular single-pole surge arrester with a varistor and spark gap connected in series in a pluggable protection module

Type	DG S 275 VA
Part No.	952 082
SPD according to EN 61643-11	Type 2
SPD according to IEC 61643-1/-11	Class II
Max. continuous operating a.c. voltage (U_c)	275 V
Max. continuous operating d.c. voltage (U_c)	350 V
Nominal discharge current (8/20 μ s) (I_n)	10 kA
Maximum discharge current (8/20 μ s) (I_{max})	20 kA
Voltage protection level (U_p)	≤ 1.5 kV
Response time (t_r)	≤ 100 ns
Maximum mains-side overcurrent protection	100 A gL/gG
Short-circuit withstand capability for max. mains-side overcurrent protection	25 kA _{rms}
Temporary overvoltage (TOV) (U_T)	335 V / 5 sec.
TOV characteristic	withstand
Operating temperature range (T_u)	-40°C...+80°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm ² solid/flexible
Cross-sectional area (max.)	35 mm ² stranded/25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	1 module(s), DIN 43880
Weight	113 g
Customs tariff number	85363030
GTIN	4013364127319
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.